








BẢO GIÁ THIẾT BỊ LƯU TRỮ NAS - THECUS





HMS xin trân trọng gửi đến Quý Đại lý bảng báo giá Thiết bị lưu trữ NAS - Thecus

Hình ảnh	Mô tả	Giá Bán Lẻ	Bảo hành	Trạng thái
SOHO/HOME				
	<p>Thecus N2200 PLUS Processor(s): Cavium SOC(Dual-Core series) Processor Memory: 256MB DDR2 Network Controller: RJ-45x2 : 10/100/1000 BASE-TX Auto MDI/MDI-X. Raid modes: RAID 0, 1, JBOD. Disk Interface: SATA I/II 3.5 “ HDD x2 or SATA 2.5” X2 Power Supply: External power adapter 12v/5A 60w (Supports 2TB 3.5" HDDx2) Form Factor: Tower</p>	2,898,000	2 năm	Có sẵn
	<p>Thecus N2200 EVO Processor(s): Cavium SOC(Dual-Core series) Processor Memory: 256MB DDR2 Network Controller: RJ-45x2 : 10/100/1000 BASE-TX Auto MDI/MDI-X. Raid modes: RAID 0, 1, JBOD. Disk Interface: SATA I/II/III 3.5 “ HDD x2 or SATA 2.5” X2 Power Supply: External power adapter 12v/5A 60w (Supports 2TB 3.5" HDDx2) Form Factor: Tower</p>	3,477,600	2 năm	Có sẵn
SBM				
	<p>Thecus N2800 Processor: Intel® Atom™ D2700 Memory: 2GB DDR3 Raid Modes: RAID 0, 1 and JBOD Network Controller: RJ-45x2: 10/100/1000 BASE-TX Auto MDI/MDI-X WOL supported Disk Interface: 2 x SATA for internal - 1 x eSATA for external Link Aggregation: Load balance, Failover, 802.3ad, Balance-XOR, Balance-TLB, Balance-ALB IP CAM Surveillance Server (module): Supports up to 5 IP cameras (via module) Power Supply: External power adaptor</p>	8,694,000	2 năm	CALL
	<p>Thecus N4100EVO Processor: Dual-core Cavium CNS3420 SoC @ 600Mhz Memory: 256MB DDR2 Network Controller: RJ-45x2: 10/100/1000 BASE-TX Auto MDI/MDI-X - WOL supported Disk Interface: 4 x SATA for internal - 1 x eSATA for external Link Aggregation: Load balance, Failover, 802.3ad, Balance-XOR, Balance-TLB, Balance-ALB IP CAM Surveillance: Supports up to 5 IP cameras (via module) Raid modes: RAID 0, 1, 5, JBOD Form Factor: Tower</p>	7,534,800	2 năm	Có sẵn

	<p>Thecus N4800 Processor: Intel® Atom™ D2700 Memory: 2GB DDR3 Network Controller: RJ-45x2: 10/100/1000 BASE-TX Auto MDI/MDI-X - WOL supported Disk Interface: 4 x SATA for internal - 1 x eSATA for external Link Aggregation: Load balance, Failover, 802.3ad, Balance-XOR, Balance-TLB, Balance-ALB IP CAM Surveillance: Supports up to 5 IP cameras (via module) Power Supply: External power adaptor Battery backup system clock Form Factor: Tower</p>	14,490,000	2 năm	Có sẵn
	<p>Thecus N4200 Pro (4 BAY) Processor: Intel® Atom™ Processor D525 Memory: 1 GB DDR-3 SDRAM Raid Modes: RAID 0, 1, 5, 6,10, JBOD Network Controller: RJ-45x2 : 10/100/1000 BASE-TX Auto MDI/MDI-X Disk Interface: SATA x4 for internal, 2x eSATA for external Link Aggregation: 802.3ad, load balance, failover, Balance-XOR, Balance-TLB, Balance-ALB Expansion Slot: PCI-e x1 IP CAM Surveillance Server (module): Supports up to 5 IP CAM Power Supply: External power adapter 19V input (support 2TB and above HDDx4) Battery backup system clock</p>	12,171,600	2 năm	Có sẵn
Enterprise - Tower				
	<p>Thecus N5550 (5 Bay) Processor: Intel® Atom™ Processor D525 Memory: 1 GB DDR-3 SDRAM Raid Modes: RAID 0, 1, 5, 6,10, JBOD Network Controller: RJ-45x2 : 10/100/1000 BASE-TX Auto MDI/MDI-X Disk Interface: SATA x4 for internal, 2x eSATA for external Link Aggregation: 802.3ad, load balance, failover, Balance-XOR, Balance-TLB, Balance-ALB Expansion Slot: PCI-e x1 IP CAM Surveillance Server (module): Supports up to 5 IP CAM Power Supply: External power adapter 19V input (support 2TB and above HDDx4) Battery backup system clock Form Factor: Tower</p>	13,620,600	2 năm	Có sẵn
	<p>Thecus N6850 Processor: Intel® Pentium® G620 2.6Ghz Memory: 2 GB DDR-3 SDRAM Raid Modes: RAID 0, 1, 5, 6,10, JBOD Network Controller: RJ-45x2 : 10/100/1000 BASE-TX Auto MDI/MDI-X Disk Interface: SATA x4 for internal, 2x eSATA for external Link Aggregation: 802.3ad, load balance, failover, Balance-XOR, Balance-TLB, Balance-ALB Expansion Slot: PCI-e x1 IP CAM Surveillance Server (module): Supports up to 5 IP CAM Power Supply: External power adapter 19V input (support 2TB and above HDDx4) Battery backup system clock</p>	27,531,000	5 năm	call

	<p>Thecus N8850 Processor: Intel® Core™ i3 2120 3.3GHz Memory: 4 GB DDR-3 SDRAM Raid Modes: RAID 0, 1, 5, 6,10, JBOD Network Controller: RJ-45x2 : 10/100/1000 BASE-TX Auto MDI/MDI-X Disk Interface: SATA x4 for internal, 2x eSATA for external Link Aggregation: 802.3ad, load balance, failover, Balance-XOR, Balance-TLB, Balance-ALB Expansion Slot: PCI-e x1 IP CAM Surveillance Server (module): Supports up to 5 IP CAM Power Supply: External power adapter 19V input (support 2TB and above HDDx4) Battery backup system clock</p>	<p>39,123,000</p>	<p>5 năm</p>	<p>call</p>
	<p>Thecus N7700 Pro Processor: Intel® Atom™ Processor D525 Memory: 1 GB DDR-3 SDRAM Raid Modes: RAID 0, 1, 5, 6,10, JBOD Network Controller: RJ-45x2 : 10/100/1000 BASE-TX Auto MDI/MDI-X Disk Interface: SATA x4 for internal, 2x eSATA for external Link Aggregation: 802.3ad, load balance, failover, Balance-XOR, Balance-TLB, Balance-ALB Expansion Slot: PCI-e x1 IP CAM Surveillance Server (module): Supports up to 5 IP CAM Power Supply: External power adapter 19V input (support 2TB and above HDDx4) Battery backup system clock</p>	<p>19,706,400</p>	<p>5 năm</p>	<p>call</p>
	<p>Thecus N10850 Processor: Intel® Xeon® E3-1225 3.1GHz Memory: 4 GB DDR-3 SDRAM Raid Modes: RAID 0, 1, 5, 6,10, JBOD Network Controller: RJ-45x2 : 10/100/1000 BASE-TX Auto MDI/MDI-X Disk Interface: SATA x4 for internal, 2x eSATA for external Link Aggregation: 802.3ad, load balance, failover, Balance-XOR, Balance-TLB, Balance-ALB Expansion Slot: PCI-e x1 IP CAM Surveillance Server (module): Supports up to 5 IP CAM Power Supply: External power adapter 19V input (support 2TB and above HDDx4) Battery backup system clock</p>	<p>44,919,000</p>	<p>5 năm</p>	<p>call</p>

	<p>Thecus N8800 Pro Processor: Intel® Core™ 2 Duo Technology Memory: 4GB DDR2 SDRAM Raid Modes: RAID 0, 1, 5, 6,10, JBOD Network Controller: RJ-45x2 : 10/100/1000 BASE-TX Auto MDI/MDI-X Disk Interface: 8 x SATA for internal, 1 x eSATA for external Link Aggregation: 802.3ad, load balance, failover, Balance-XOR, Balance-TLB, Balance-ALB Expansion Slot: PCI-e x1 IP CAM Surveillance Server (module): Supports up to 10 IP CAM Power Supply:Redundant power supply 350W Form Factor: 2U Rack Mount</p>	36,225,000	2 năm	Có sẵn
	<p>Thecus 1U4200XXX Processor: Intel® Atom™ D525 Memory: 1GB DDR3 SODIMM Raid Modes: RAID 0, 1, 5, 6, 10 and JBOD Network Controller: RJ-45x2: 10/100/1000 BASE-TX Auto MDI/MDI-X Disk Interface: 4 x SATA for internal - 1 x eSATA for external Link Aggregation: Load balance, Failover, 802.3ad, Balance-XOR, Balance-TLB, Balance-ALB IP CAM Surveillance Server (module): Power Supply: 200W Power supply (1U4200XXXS) - 250W Redundant power supply (1U4200XXXR) Battery backup system clock</p>	17,388,000	2 năm	Có sẵn
	<p>Thecus N16000 Processor: Intel® Xeon® Processor X3480 Processor + Intel 3450 chipset Memory: 8GB DDR3 SDRAM Raid Modes: RAID 0, 1, 5, 6, 10, 50, 60 and JBOD Network Controller: RJ-45x3 : Intel 82574L 10/100/1000 BASE-TX Auto MDI/MDI-X WOL supported Disk Interface: SATA/SAS (x16) via backplane Link Aggregation: 6 modes supported IP CAM Surveillance Server (module): Supports up to 10 IP cameras (via module) Battery backup system clock</p>	108,675,000	3 năm	CALL
	<p>Thecus N16000V Processor Intel® Xeon® Processor X3480 Processor + Intel 3450 chipset Memory: 4GB DDR3 SDRAM Raid Modes: RAID 0, 1, 5, 6, 10, 50, 60 and JBOD Network Controller: RJ-45x3 : Intel 82574L 10/100/1000 BASE-TX Auto MDI/MDI-X WOL supported Disk Interface: SATA/SAS (x16) via backplane Link Aggregation: 6 modes supported IP CAM Surveillance Server (module): Supports up to 10 IP cameras (via module) Battery backup system clock</p>	92,736,000	3 năm	CALL

	<p>Thecus N8900 Processor: Intel® Core™ i3-2120 Memory: 8GB DDR3 SDRAM Raid Modes: RAID 0, 1, 5, 6, 10, 50, 60 and JBOD Network Controller: RJ-45x3: Intel 82574L 10/100/1000 BASE-TX Auto MDI/MDI-X WOL supported Disk Interface: 8 x SATA for internal - 1 x eSATA for external Link Aggregation: Load balance, Failover, 802.3ad, Balance-XOR, Balance-TLB, Balance-ALB IP CAM Surveillance Server (module): Supports up to 10 IP cameras (via module) Power Supply: Redundant power supply 500W or more</p>	57,380,400	3 năm	CALL
	<p>Thecus N8900 V Processor: Intel® Pentium® Processor G620 @ 2.6GHz Memory: 2GB DDR3 SDRAM Raid Modes: RAID 0, 1, 5, 6, 10, 50, 60 and JBOD Network Controller: RJ-45x3: Intel 82574L 10/100/1000 BASE-TX Auto MDI/MDI-X WOL supported Disk Interface: 8 x SATA for internal - 1 x eSATA for external Link Aggregation: Load balance, Failover, 802.3ad, Balance-XOR, Balance-TLB, Balance-ALB IP CAM Surveillance Server (module): Supports up to 10 IP cameras (via module) Power Supply: Redundant power supply 500W or more</p>	48,686,400	3 năm	CALL
	<p>Thecus N8200 XXX Processor: Intel® Atom™ D525 Memory: 1GB DDR3 SODIMM Raid Modes: RAID 0, 1, 5, 6,10, JBOD Network Controller: RJ-45x2 : 10/100/1000 BASE-TX Auto MDI/MDI-X Disk Interface: 8 x SATA for internal, 1 x eSATA for external Link Aggregation: 802.3ad, load balance, failover, Balance-XOR, Balance-TLB, Balance-ALB Expansion Slot: PCI-e x1 IP CAM Surveillance Server (module): Supports up to 10 IP CAM Power Supply: External power adapter 19V input (support 2TB and above HDDx4)</p>	33,327,000	3 năm	CALL
	<p>Thecus N12000 V Processor: Intel® Xeon® Processor X3470 Processor + Intel 3450 chipset Memory: 8GB DDR3 SDRAM Raid Modes: RAID 0, 1, 5, 6, 10 and JBOD Network Controller: RJ-45x2: 10/100/1000 BASE-TX Auto MDI/MDI-X Disk Interface: 12 x SATA for internal Link Aggregation: Load balance, Failover, 802.3ad, Balance-XOR, Balance-TLB, Balance-ALB IP CAM Surveillance Server (module): Power Supply: 200W Power supply (1U4200XXXS) - 250W Redundant power supply (1U4200XXXR) Battery backup system clock</p>	78,246,000	3 năm	CALL



Thecus N12000
Processor: Intel® Xeon® Processor X3470 Processor + Intel 3450 chipset
Memory: 8GB DDR3 SDRAM
Raid Modes: RAID 0, 1, 5, 6, 10 and JBOD
Network Controller: RJ-45x2: 10/100/1000 BASE-TX Auto MDI/MDI-X
Disk Interface: 12 x SATA for internal
Link Aggregation: Load balance, Failover, 802.3ad, Balance-XOR, Balance-TLB, Balance-ALB
IP CAM Surveillance Server (module):
Power Supply: 200W Power supply (1U4200XXXS) - 250W
Redundant power supply (1U4200XXXR)
Battery backup system clock

89,838,000

3 năm

CALL

Ghi chú:

- * Giá trên không bao gồm thuế VAT 10% và có thể thay đổi mà không kịp báo trước . Để có giá chính xác xin vui lòng liên hệ lại .
- * Thanh toán bằng tiền mặt hoặc chuyển khoản theo tỉ giá thoả thuận tại thời điểm xuất hoá đơn .

Mọi chi tiết xin vui lòng liên hệ :

(Mr) Lê Hoàng Hải

Bussiness Department.

[t]: 0937 10 38 39

[e]:hai-lh@hms.vn